

# SAFETY DATA SHEETS

**This SDS packet was issued with item:**

078849543

**The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).**

078849469 078849477 078849527

# SAFETY DATA SHEET

Conforms with OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



Product: CryoSolutions Nitrous Oxide Cartridge

Revision Date: 11/03/2015

## SECTION 1 - IDENTIFICATION

### Product Identifier

**Product Name:** CryoSolutions Nitrous Oxide Cartridge  
(Compressed, content not exceeding 50ml)

**Product Code:** 33516, 33517, 33518

### Recommended Use of the Chemical and Restrictions on Use

**Recommended Use:** Special Nitrous Oxide gas cartridges (23.5gr.) for the use on CryoSolutions system with corresponding mounting support only.

**Restrictions on Use:** Use only as directed.

### Details of the Supplier

**Manufactured for:** Integra York PA, Inc.  
589 Davies Dr.  
York, PA 17402 USA  
1-866-854-8300

### Emergency Phone Number

**24-Hour Number:** 1-800-535-5053

**International:** 1-352-323-3500

## SECTION 2 – HAZARDS IDENTIFICATION

### Classification

Hazard Class	Category
Gases under pressure	Liquefied gas
Oxidizing gases	1

### Label Elements

**Hazard Symbols(s):**



**Signal Word(s):** Danger

### **Hazard Statement(s):**

Contains gas under pressure; may explode if heated.  
May cause or intensify fire; oxidizer.  
Heating may cause an explosion  
Harmful if inhaled

# SAFETY DATA SHEET

Conforms with OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



**Product:** CryoSolutions Nitrous Oxide Cartridge

**Revision Date:** 11/03/2015

## **Precautionary Statements:**

Keep out of reach of children.  
Keep away from combustible materials.  
Keep valves and fittings free from oil and grease.  
In case of fire: Stop leak if safe to do so.  
Store in a well-ventilated place.  
Protect from direct sunlight.

## **Other Hazards**

May cause asphyxiation in high concentrations.

## SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Wt. %
Dinitrogen oxide (Nitrous Oxide)	10024-97-2	100

Does not contain any other components or impurities which could affect the classification of this product.

## SECTION 4 – FIRST AID MEASURES

### **First Aid Measures**

#### **Inhalation:**

High concentrations can cause asphyxiation. Symptoms can include loss of mobility and consciousness. The victim does not notice the asphyxiation. In low concentrations can cause narcotic effects. Symptoms can include dizziness, headache, nausea and coordination problems. Immediately remove victim to uncontaminated area. The victim should be made to wear appropriate NIOSH approved respiratory equipment. Keep victim warm and rested. Consult a doctor. Attempt artificial respiration if the victim stops breathing.

**Eye Contact:** Immediately flush eyes thoroughly with water for at least 15 minutes.

**Ingestion:** Ingestion is not seen as a possible method of exposure.

**Skin:** Contact with liquid can cause cold burns/frost bite. Spray any cold burns immediately with water for at least 15 minutes. Cover with a sterile dressing. Consult a doctor.

### **Most Important Symptoms and Effects (Acute and Delayed)**

#### **Potential Acute Health Effects**

**Eye Contact:** No known significant effects or critical hazards.

**Inhalation:** Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.

**Skin Contact:** No known significant effects or critical hazards.

**Frostbite:** Try to warm up the frozen tissues and seek medical attention.

# SAFETY DATA SHEET

Conforms with OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



Product: CryoSolutions Nitrous Oxide Cartridge

Revision Date: 11/03/2015

**Ingestion:** Can cause central nervous system (CNS) depression. As this product is a gas, refer to the inhalation section.

### Over-exposure Signs/Symptoms

**Eye Contact:** No specific data.

**Inhalation:** Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness.

**Skin Contact:** No specific data.

**Ingestion:** No specific data.

### Indication of any Immediate Medical Attention and Special Treatment Needed

**Notes to physician:** In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific Treatments:** No specific treatment.

**Protection of first-aiders:** No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## SECTION 5 – FIRE-FIGHTING MEASURES

### Extinguishing Media

**Suitable:** All known extinguishants can be used.

**Unsuitable:** None identified.

### Specific Hazards Arising from Chemical

- Supports combustion. Non-flammable.
- Exposure to fire may cause cylinder to burst/explode.
- If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: nitric oxide, nitrogen dioxide.

### Protective Equipment and Precautions for Firefighters

- Use self-contained breathing apparatus and chemically protective clothing.
- Move away from the container and cool with water from a safe position.

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment, and Emergency Procedures

# SAFETY DATA SHEET

Conforms with OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



**Product:** CryoSolutions Nitrous Oxide Cartridge

**Revision Date:** 11/03/2015

**Personal Precautions:** Ensure adequate ventilation. Remove ignition sources.

**Environmental Precautions:** Attempt to stop gas release. Prevent from entering sewer systems, basements, work pits or any other areas where accumulation could be hazardous.

## **Methods and Material for Containment and Cleaning Up**

Ventilate the area.

## **SECTION 7 – HANDLING AND STORAGE**

### **Precautions for Safe Handling**

#### **Handling:**

- Only use equipment suitable for this product and the pressure and temperature specified.
- Keep away from ignition sources (including electrostatic discharges).
- Do not puncture or heat over 50°C.
- Protect from physical damage.
- Never use direct flame or electrical heating devices to raise the pressure of a cylinder.
- Never attempt to refill an empty cylinder.
- Emerging gas will cause the cylinder to freeze.
- Do not touch a discharging or recently discharged cylinder with bare hands.
- Never attempt to transfer gases from one cylinder to another.
- Do not use the cylinder as a roller or support, or for any other purpose than to contain the gas as supplied.
- Do not subject cylinder to mechanical shocks which may cause damage to their integrity.

### **Conditions for Safe Storage, Including any Incompatibilities**

#### **Storage Conditions:**

- Keep out of reach of children.
- Store the containers in a well-ventilated place at less than 50°C.
- Store cylinder in a location free from risk of fire and away from sources of heat and ignition.
- Periodically check cylinder for general conditions and leakage.
- Do not store containers in conditions likely to encourage corrosion.

**Incompatible Materials:** None identified.

## **SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION**

### **Control Parameters**

#### **Exposure Guidelines:**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH REL
Nitrous Oxide	50 ppm 8hr TWA	Not available	25 ppm (TWA)

### **Appropriate Engineering Controls**

# SAFETY DATA SHEET

Conforms with OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



**Product:** CryoSolutions Nitrous Oxide Cartridge

**Revision Date:** 11/03/2015

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

## **Environmental Exposure Controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **Individual Protection Measures**

**Respiratory Protection:** Ensure adequate ventilation.

**Skin and Body Protection:** Wearing of appropriate chemical resistant gloves is recommended.

**Eye/Face Protection:** Protect eyes, skin, and face from liquid splashes.

**General Work/Hygienic Practices:** Do not smoke while handling the product.

## **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Colorless compressed gas

**Odor:** Slightly sweet odor

**Odor threshold:** Not determined

**Molecular Weight:** 44

**pH:** Not determined.

**Melting point:** -90.81°C/-131.8°F

**Initial boiling point and boiling range:** -88.5°C/-127.3°F; range not determined

**Critical Temperature:** 36.4°C/97.5°F

**Flash point:** Oxidation agent.

**Evaporation rate:** Not determined

**Flammability (solid, gas):** Extremely flammable in the presence of the following materials or conditions: reducing materials and combustible materials.

**Upper/lower flammability or explosive limits:** Not determined

**Vapor pressure (20°C):** 50.8 bar/736 psig at 20°C/68°F

**Vapor density:** Not determined

# SAFETY DATA SHEET

Conforms with OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



**Product:** CryoSolutions Nitrous Oxide Cartridge

**Revision Date:** 11/03/2015

**Relative density, gas (air = 1):** 1.5

**Solubility in water (mg/l):** 2.2

**Partition coefficient (n-octanol/water):** Not determined

**Auto-ignition temperature:** Not applicable.

**Decomposition temperature:** Not determined

**Viscosity:** 0.0145 cP@25C

**Other information:** Gas/vapors are heavier than air. They can accumulate in confined spaces, especially at floor level or in lower-level areas

## SECTION 10 – STABILITY AND REACTIVITY

**Reactivity:** No additional information.

**Chemical stability:** The decomposition of nitrous oxide is exothermic and irreversible, leading to considerable increase in pressure.

**Possibility of hazardous reactions:**

Hazardous reactions or instability may occur under certain conditions of storage or use.

**Conditions may include the following:** contact with combustible materials

**Reactions may include the following:** risk of causing fire.

**Conditions to avoid:**

At temperatures of over 575°C, at atmospheric pressure, nitrous oxide breaks down into nitrogen and oxygen. Heat.

Under pressure nitrous oxide can also decompose into nitrogen and oxygen at temperatures above 300°C. Heat.

**Incompatible materials:**

- Can violently react with combustible materials.
- Can violently react with reducing agents.
- Violently oxidizes organic materials.

**Hazardous decomposition products:**

Thermal decomposition yields toxic products which can be corrosive in the presence of moisture. In the presence of catalysts (e.g. halogen compounds, mercury, nickel, platinum), decomposition increases and decomposition can occur at even lower temperatures.

## SECTION 11 – TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects

There is no scientific consensus as to possible toxic effects, but some studies indicate that nitrous oxide may cause damage to the reproduction system, the upper respiratory tract, or the central nervous system.

# SAFETY DATA SHEET

Conforms with OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



Product: CryoSolutions Nitrous Oxide Cartridge

Revision Date: 11/03/2015

## SECTION 12 – ECOLOGICAL INFORMATION

### Ecotoxicity:

**Global Warming Potential [CO<sub>2</sub>=1]:** 298

**Persistence and degradability:** No additional information.

**Bioaccumulative potential:** No additional information.

**Mobility in soil:** No additional information.

**Other adverse effects:** No additional information.

## SECTION 13 – DISPOSAL CONSIDERATIONS

### General:

Release into the atmosphere in a well ventilated place.  
Avoid releasing large quantities into the atmosphere.  
Do not discharge into any place where its accumulation could be dangerous.

### Disposal Methods:

Dispose of emptied cylinders only.  
Cylinders are made of recyclable steel and hence a valuable resource. Emptied cylinders should therefore always be recycled.  
Adhere to local waste regulations when disposing of emptied cylinders. Never dispose of cylinders in an uncontrolled manner (e.g. dumping at sea).

## SECTION 14 – TRANSPORT INFORMATION

### Ground or sea transport

**U.S. DOT 49 CFR 172.101 :** ORM-D Consumer Commodity

### Air shipment

**PROPER SHIPPING NAME :** Nitrous oxide

**ID NUMBER :** UN1070

**HAZARD CLASS OR DIVISION :** 2.2

**LABELING REQUIREMENTS :** 2.2; 5.1

## SECTION 15 – REGULATORY INFORMATION



# SAFETY DATA SHEET

Conforms with OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



**Product:** CryoSolutions Nitrous Oxide Cartridge

**Revision Date:** 11/03/2015

OSHA Hazard Communication Standard (29 CFR 1910.1200) Hazard Class(es): Compressed Gas; Oxidizer.

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification: Sudden Release of Pressure Hazard; Fire Hazard.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65) WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

## SECTION 16 – OTHER INFORMATION

Can cause asphyxiation in high concentrations.  
The risk of asphyxiation is often overlooked and must be made clear when training employees.  
Contact with liquid can cause cold burns/frost bite.

**Issue Date:** 11/03/2015

**Revision Date:** 11/03/2015

Liability Disclaimer: SDS information is provided based on OSHA's Hazardous Communication Regulation and for use of the persons required to receive this information under this regulation. The information is neither designed nor recommended for any other use or for use by any other person, including compliance with other laws. Integra York PA, Inc. (the "Company") does not warrant the suitability for use of this SDS for any other material or product not specifically identified herein. The Company does not warrant the accuracy or authenticity of this SDS unless it has been obtained directly from the Company, or posted or viewed on a Company website. This SDS is based on information that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under the Company's control, each user is responsible for making their own determination as to the safe and proper handling of this material in their own particular use of this material. The Company makes no representation or warranty, either expressed or implied, including as to merchantability or fitness for a particular purpose.